



Gooseneck

Standard Features

Frame

4"x8" Tube Main Frame (All Sizes)
Crossmembers (16" O/C)
Steel Tube Roof Bows (16" O/C)
Steel Tube Wall Posts (16" O/C)

Interior

3/4" Drymax Flooring
3/8" Drymax Wall Liner

Electrical

2-12V L.E.D. Interior Lights w/ 1 Switch
7 Way Electrical Plug
L.E.D. Strip Tail & Clearance Lights (7/Side)
L.E.D. Mid-Ship Turn Signals

Axles/Wheels

All Wheel Electric Brakes w/ Break-Away
Dexter Torsion Axles w/ E-Z Lube Hubs
Radial Tires on Silver Modular Steel Wheels

Safety/Warranty

1 Year Limited Warranty
3 Year Structural Warranty
D.O.T / C.S.A Approved Safety Equipment

Exterior

(4) 5K D-Rings
.030 Aluminum Exterior w/ Screwed Seams
1 Piece Aluminum Roof
24"x36" ATP Baggage Door in Stoneguard
3" Top & Bottom Trim w/ Cast Rear Corners
48" Side Door w/ Stepwell (Aluminum Framed)
5000# Ramp Door w/ Beavertail
6" Barrier Tape
Aluminum Door Hardware
Aluminum Door Holdback
Brite Front Vertical Corners
Brite Insert Between Front Corner Castings
Cast Aluminum Front & Rear Corners
Dual Post 2-Speed Landing Gear
Flat Top w/ Tapered Side Upper Deck
Framed for Roof Vent
Framed for Roof Vent
Gooseneck Coupler OR Fifthwheel
Grab Handle on Side Door & Ramp Door
Roof Vent or Flo-Thru Vents
Smooth Aluminum Exterior Fenders