



# Endeavor

## Standard Features

### Frame

All Aluminum Tube Frame Construction  
 Aluminum I-Beam Crossmembers (24" O/C)  
 Aluminum Tube Roof Bows (24" O/C)  
 Aluminum Tube Wall Posts (16" O/C)

### Interior

3/4" Drymax Flooring  
 3/8" Drymax Wall Liner

### Electrical

L.E.D. Taillights & Bullet Marker Lights (4/Side)

### Axles/Wheels

Dexter Spring Axles w/ 4" Drop  
 ST205/75R15" Radials on Aluminum Wheels

### Safety/Warranty

1 Year Limited Warranty  
 3 Year Structural Warranty  
 D.O.T / C.S.A Approved Safety Equipment

### Exterior

.030 Screwless Exterior  
 1 Pc. Aluminum Roof  
 24" Slanted or Straight Wedge Front  
 24" Stone Guard  
 3" Top & Bottom Trim (Riveted)  
 Aluminum Door Hold Backs  
 Aluminum Framed Doors  
 Brite Aluminum Nose on Wedge  
 Color Matched Rear Corners  
 Framed for Roof Vent  
 Roof Vent or Flo-Thru Vents  
 Smooth Aluminum Fenders  
 Zinc Hardware Aluminum hinges

## Axles Features

### Single Axles

2" Couplers  
 (1) 12V L.E.D. Dome Lights w/ Switch

### Tandem Axles

2-5/16" Coupler on TA Models (and 7 wide SAE)  
 (2) 12V L.E.D. Dome Lights w/ Switch

## Size Features

5' Wide	6' Wide	7' Wide
Single Rear Door or Ramp	2" x 3" Aluminum Tube Main Frame SA	2"x 5" Double Hollow Tube Main Frame
2" x 3" Aluminum Tube Main Frame SA	2" x 4" Aluminum Tube Main Frame on 6' (T A)	32" Side Door
-	32" Side Door	Double Doors or Ramps
-	Double Doors or Ramp Door	Wide Track Axle(s)